



## Welding Blankets and Welding Curtains

Fires can be accidentally started by welding sparks which smoulder and burst into flames. This can sometimes happen when a welding, grinding or gas cutting operation has finished and premises left unattended. Avoid this serious safety hazard by using BRIDELA™ welding blankets and welding curtains.

The welding blankets can protect workers and have the added benefit of shielding flammable materials, machinery, plant and equipment from molten metal globules, spatter, etc. They may be reusable, dependent upon the application.

The welding curtains can be used to isolate an area, so offering protection to workers from welding sparks and light welding spatter and, if correctly positioned, can also assist in the protection of personnel working nearby from arc-eye or weld-flash. For use in well-ventilated areas.

- Brass metal eyelets (grommets) can be fitted to the edge(s) of these products to facilitate easy suspension/securement. Alternatively, in-built sleeving can be provided for the insertion of metal suspension bars, etc.
- Can be manufactured into specific sized welding blankets / welding curtains or, alternatively, supplied in roll form (to be cut to size by end user)
- All materials are completely non-asbestos
- **Manufactured in the United Kingdom**

Reinforced P.V.C. Welding Curtains	Neoprene Curtains & Blankets	Weld 1000 Welding Blankets	Silica Welding Blankets
Product Ref: OB2/XT	Product Ref: DHO/651 - medium weight DHO/011 - heavy weight	Product Ref: Z1687/409	Product Ref: IT/761/BS - medium weight TLW/2211 - heavy weight
Protection from grinding sparks and flying particles	Protection from welding sparks and light to medium spatter	Protection from molten metal globules / spatter up to 1000°C / 1832°F	Protection from molten metal globules / spatter up to 1000°C / 1832°F
UV absorbency assists in the prevention of arc-eye / weld-flash	Good resistance to oils, greases and vapours	Ideal for cutting operations	Ideal for cutting operations and heavy duty welding protection
Translucency offers two-way vision for safety and supervision	High abrasion resistance	Superior tensile strength and abrasion resistance	Abrasion resistant finish
Nylon reinforcement offers excellent tear resistance	Medium weight material (DHO/651) passed indicative test to BS 476 part 20	Material certified to BS 476 part 4 / Class '0' and passed indicative test to BS 476 part 20	Medium weight material (IT/761/BS) certified to BS 476 part 4 / Class '0'
Most beneficial as a vertical barrier	Can be used as a vertical or horizontal welding barrier	Most beneficial as a horizontal welding barrier	Heavy weight material (TLW/2211) certified to BS 476 part 4 / Class '0' and BS 476 part 7
Available in two colours - green or red	Also suitable as a fire cavity barrier	Also suitable as a fire cavity barrier	High flexibility and drapeability
Material certified to BS EN 1598 (Health and Safety in Welding and Allied Processes)	Non-combustible	Non-combustible	Non-combustible

**AIR SPACE** - We recommend that a sufficient air space is provided between these welding fabrics and the surface you are protecting, both in horizontal and vertical positions.